PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 :
H04L 12/56, 12/28, H04M 7/00

A1

(11) International Publication Number: **WO 00/35153**

(43) International Publication Date: 15 June 2000 (15.06.00)

(21) International Application Number: PCT/US99/27400

(22) International Filing Date: 19 November 1999 (19.11.99)

(30) Priority Data:

60/110,972	4 December 1998 (04.12.98)	US
09/415,907	8 October 1999 (08.10.99)	US

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(71) Applicant *(for all designated States except US)*: NORTEL NETWORKS CORPORATION [CA/CA]; World Trade Center of Montreal, 380 St. Antoine Street West, 8th floor, Montreal, Quebec H2Y 3Y4 (CA).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: BARANY, Peter [US/US]; 830 Hills Creek Drive, McKinney, TX 75070 (US). BHARATIA, Jayshree [IN/US]; 1717 Panigo Drive, Plano, TX 75075 (US).

(74) Agents: ANDERSON, Matthew, S. et al.; Felsman, Bradley, Vaden, Gunter & Dillon, L.L.P., 201 Main Street, Suite 1600, Fort Worth, TX 76102 (US).

(54) Title: SYSTEM AND METHOD FOR IMPLEMENTING XoIP OVER ANSI-136-A CIRCUIT-SWITCHED/PACKET-SWITCHED MOBILE COMMUNICATIONS NETWORKS



(57) Abstract

The SS7 interface of a conventional GPRS-136 or GPRS-136HS network is replaced with an IP interface. An IP interface is placed between the ANSI TIA/EIA-41 circuit-switched network and the GPRS-136 packet-switched network. This interface can handle both signaling and bearer traffic and thereby overcomes the limitations imposed by the current SS7 interface, which can handle only signaling.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	**ES**	Spain	**LS**	Lesotho	**SI**	Slovenia
AM	Armenia	**FI**	Finland	**LT**	Lithuania	**SK**	Slovakia
AT	Austria	**FR**	France	**LU**	Luxembourg	**SN**	Senegal
AU	Australia	**GA**	Gabon	**LV**	Latvia	**SZ**	Swaziland
AZ	Azerbaijan	**GB**	United Kingdom	**MC**	Monaco	**TD**	Chad
BA	Bosnia and Herzegovina	**GE**	Georgia	**MD**	Republic of Moldova	**TG**	Togo
BB	Barbados	**GH**	Ghana	**MG**	Madagascar	**TJ**	Tajikistan
BE	Belgium	**GN**	Guinea	**MK**	The former Yugoslav Republic of Macedonia	**TM**	Turkmenistan
BF	Burkina Faso	**GR**	Greece			**TR**	Turkey
BG	Bulgaria	**HU**	Hungary	**ML**	Mali	**TT**	Trinidad and Tobago
BJ	Benin	**IE**	Ireland	**MN**	Mongolia	**UA**	Ukraine
BR	Brazil	**IL**	Israel	**MR**	Mauritania	**UG**	Uganda
BY	Belarus	**IS**	Iceland	**MW**	Malawi	**US**	United States of America
CA	Canada	**IT**	Italy	**MX**	Mexico	**UZ**	Uzbekistan
CF	Central African Republic	**JP**	Japan	**NE**	Niger	**VN**	Viet Nam
CG	Congo	**KE**	Kenya	**NL**	Netherlands	**YU**	Yugoslavia
CH	Switzerland	**KG**	Kyrgyzstan	**NO**	Norway	**ZW**	Zimbabwe
CI	Côte d'Ivoire	**KP**	Democratic People's Republic of Korea	**NZ**	New Zealand		
CM	Cameroon			**PL**	Poland		
CN	China	**KR**	Republic of Korea	**PT**	Portugal		
CU	Cuba	**KZ**	Kazakstan	**RO**	Romania		
CZ	Czech Republic	**LC**	Saint Lucia	**RU**	Russian Federation		
DE	Germany	**LI**	Liechtenstein	**SD**	Sudan		
DK	Denmark	**LK**	Sri Lanka	**SE**	Sweden		
EE	Estonia	**LR**	Liberia	**SG**	Singapore		

SYSTEM AND METHOD FOR IMPLEMENTING XoIP OVER ANSI-136-A CIRCUIT-SWITCHED/PACKET-SWITCHED MOBILE COMMUNICATIONS NETWORKS

Description

Technical Field

The present invention generally relates to improved mobile telecommunications systems and in particular to improved packet-switched wireless/wired communication systems. Still more particularly, the present invention relates to an improved packet-switched telecommunications system which utilizes Internet Protocol packet communications.

Background Art

The written description utilizes a large number of acronyms to refer to components, methods and services. Although these acronyms, and the corresponding protocols and technologies, are known to those of skill in the art, for purposes of this discussion and convenience for the reader, acronyms will be defined as follows:

AMPS	Advanced Mobile Phone Service. TIA analog cellular, and all standards that retain compatibility with it (NAMPS, D-AMPS, CDMA)
ANSI	American National Standards Institute.
BSS	Base Station System
DCCH	Digital Control Channel. The control channel used by IS-136 and TIA/EIA-136 D-AMPS systems.
DTC	Digital Traffic Channel
DMS	Digital Multiplex Switch
EIA	Electronics Industry Association
Gateway MSC	An MSC designed to provide a gateway between a TIA/EIA-136 / ANSI-41 network and a GPRS-136 network.

GGSN	Gateway GPRS Support Node
GPRS	Generalized Packet Radio Service. A GSM-based packet data protocol.
GSM	Global System for Mobile Communications.
GTP	GPRS Tunnelling Protocol
IMT	International Mobile Telecommunications
ISUP	ISDN User Part. SS7 signaling between switches.
MDIS	Mobile Data Interface System
MGCP	Media Gateway Control Protocol
MSC	Mobile Switching Center
MSC-G	Gateway MSC.
MSC-H	Home MSC.
MSC-O	Originating MSC.
MSC-V	Visited MSC. The MSC in which a mobile is currently registered.
PDN	Public Data Network
POTS	Plain Old Telephone Service
PSTN	Public Switched Telephone Network
Protocol	A specification of the messages used to communicate over one or more interfaces.
RTP	Real-Time Transport Protocol
SCP	Signal Control Point
SGSN	Serving GPRS Support Node
STP	Signal Transfer Point
SS7	Signaling System Number 7
TDMA	Time Division Multiple Access. A modulation technique used, *e.g.*, by GSM.
TIA	Telecommunications Industry Association
TIA/EIA-136	TDMA air interface standard. Replaces IS-136.
XoIP	Communications via Internet Protocol, where X can represent voice, data, video, etc.

In the current version of the ANSI TIA/EIA-136 and ANSI TIA/EIA-41 standards, the Digital Control Channel (DCCH) and Digital Traffic Channel (DTC) support speech, asynchronous circuit-switched data, and G3 Fax services.

All three of these services are circuit-switched oriented. Revisions are now being made to the ANSI TIA/EIA-136 standard to produce ANSI TIA/EIA-136-A and ANSI TIA/EIA-136-B. ANSI TIA/EIA-136-A will specify a packet-switched data service known as "136+"or GPRS-136. ANSI TIA/EIA-136-B will specify a high-speed packet-switched service known as "136HS" or GPRS-136HS. The core technology for both of these packet-switched services is based on GPRS and EGPRS, respectively. These are ETSI GSM standards.

Figure 1 shows a conventional GPRS-136-based network where voice and circuit-switched data is still supported by the circuit switched network **103/104** but packet-switched data is supported by the GPRS-136 packet data network **106.** Gateway MSC (G-MSC) **103** is a new functional entity standardized for GPRS-136, which is an MSC having the capability to provide a gateway to GPRS-136 network. Hence, G-MSC can be viewed as a part of MSC or a separate network Node. If it is considered a separate node, the SS7 'E' interface is used to exchange signaling messages with MSC.

In **Figure 1**, a mobile station MSx **101**, which incorporates a vocoder and handles voice or circuit-switched data calls, communicates over the air with a BSSx switch **102**, which supports voice and/or circuit switched data. The BSSx **102** communicates via both a T1 bearer traffic interface and a signaling interface A with a gateway mobile switching center **103.** The SS7 network **104** is connected, in turn, with a terminating network **105** and a GPRS-136 network **106.** Note that connection **Gs'**, between the SS7 network **104** and the GPRS-136 network **106,** is a signaling interface only.

A GPRS-136 mobile station MSy **107**, also incorporating a vocoder and configured to support voice and/or packet-switched data, communicates over the air with a BSSy switch **108**, which supports packet data. The BSSy **108** communicates over a bearer traffic interface **Gb'** with the GPRS-136 network **106**. For voice calls, the vocoder of MSy **107** communicates with the BSSx switch **102**, as described above.

GPRS-136 network **106** is connected to Public Data Network (PDN) **109**. The PDN includes any destination terminal equipment **110**.

TDMA service operators have expressed a desire to implement XoIP over the GPRS-136 network (where X can represent voice, data, video, etc., *e.g.*, VoIP). XoIP can be implemented over the circuit-switched or packet-switched air interface. However, the current interface Gs' to the GPRS-136 packet-switched network is standardized for signaling only and is implemented via SS7. Therefore, if the circuit-switched air interface is to be used, this is a problem, because XoIP involves the transmission of both signaling and bearer traffic. Therefore, the SS7 interface is inappropriate and an XoIP solution utilizing the GPRS-136 network would be greatly desired.

Disclosure of Invention

It is therefore one object of the present invention to provide an improved mobile telecommunications system.

It is another object of the present invention to provide an improved packet-switched mobile telecommunications system.

It is yet another object of the present invention to provide an improved packet-switched telecommunications system which utilizes Internet Protocol packet communications.

The foregoing objects are achieved as is now described. According to the preferred embodiment of the invention, the SS7 interface of a conventional GPRS-136 network is replaced with an IP interface. In this embodiment. an IP interface is placed in parallel with the Gs' interface between the DMS MSC/G-MSC and the GPRS-136 packet-switched network. This interface can handle both signaling and bearer traffic and thereby overcomes the limitations imposed by the current SS7 interface, which can handle only signaling.

The above as well as additional objectives, features, and advantages of the present invention will become apparent in the following detailed written description.

Brief Description of Drawings

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with August 18, 1999the accompanying drawings, wherein:

Figure 1 depicts a conventional GPRS network;

Figure 2 is an improved GPRS/IP network, in accordance with a preferred embodiment of the invention;

Figure 3 shows a diagram of the delivery of a telephone call or circuit-switched data transaction originating in an ANSI-136-A voice or circuit-switched data mobile station to an IP network, in accordance with a preferred embodiment of the invention;

Figure 4 shows a diagram of the delivery of a telephone call or circuit-switched data transaction originating in an ANSI-136-A voice or circuit-switched data mobile

station to another ANSI-136/ANSI-41 network (or vice versa) via an IP network, in accordance with a preferred embodiment of the invention; and

Figure 5 shows a diagram of the delivery of a telephone call or circuit-switched data transaction originating in an ANSI-136-A voice or circuit-switched data mobile station to a Circuit-Switched Network (SCN) such as PSTN, ISDN via an IP network, in accordance with a preferred embodiment of the invention.

Best Mode for Carrying Out the Invention

With reference now to the figures, and in particular with reference to **Figure 2**, according to the preferred embodiment, the GS' interface of the conventional GPRS-136 network is improved to support bearer data and call control signaling in addition to existing signaling. The improved GS' interface also replaces transport of this interface from SS7 with IP. Further, the preferred embodiment bypasses the vocoder which currently is required by the G-MSC/MSC. It should be noted that where "GPRS-136" is used below, it is intended to apply to the entire GPRS-136 "family", including GPRS, EGPRS, GPRS-136, and GPRS-136HS. Further, those of skill in the art will recognize that the innovative system and techniques described below will also apply to other wireless standards and technologies.

The preferred embodiment is thus a great improvement over the conventional GPRS-136 network shown in **Figure 1**, in which the current interface (Gs') between the Gateway MSC (G-MSC) and SGSN node of packet data network is standardized for signaling only and is implemented via SS7.

As shown in **Figure 2**, a new functional node, also known as PSTN gateway **212**, is defined between the traditional network and the IP network **211**. Different interfaces of the PSTN gateway are currently being standardized in IETF (Internet Engineering Task Force), and specific implementations are within the ability of one of ordinary skill in the art. A standard device control protocol can be used between its three functional entities, the Media Gateway, (MG) the Media Gateway Controller

(MGC), and Call Agent (CA) or Signaling Gateway (SG). In all figures, CA is assumed to support the functionality of MGC.

According to the preferred embodiment, there is no change in the way voice is handled, from an access point of view, i.e., there are no changes required at BSS or Mobile. Signaling for a voice call is still handled by A interface and bearer is transported using T1 links.

With reference to **Figure 2**, voice and circuit-switched data is still supported by the circuit switched network **203/204** and packet-switched data is supported by the GPRS-136 packet data network **206**. Gateway MSC (G-MSC) **203** provides a gateway to GPRS-136 network.

In **Figure 2**, a mobile station MSx **201**, which can incorporate a vocoder and handles voice or circuit-switched data calls, communicates over the air with a BSSx switch **202**, which supports voice and/or circuit switched data. The BSSx **202** communicates via both a T1 bearer traffic interface and a signaling interface A with a gateway mobile switching center **203**. The SS7 network **204** is connected, in turn, with a GPRS-136 network **206**. Note that connection **Gs'**, between the SS7 network **204** and the GPRS-136 network **206**, is a signaling interface only.

A GPRS-136 mobile station MSy **207**, also incorporating a vocoder and configured to support voice and/or packet-switched data, communicates over the air with a BSSy switch **208**, which supports packet data. The BSSy **208** communicates over a bearer traffic interface **Gb'** with the GPRS-136 network **206**. For voice calls, the vocoder of MSy **207** communicates with the BSSx switch **202**, as described above.

GPRS-136 network **206** is connected to PDN/IP network **214**. The PDN/IP network **214** is connected to terminating network **215**.

According to the preferred embodiment, for outgoing calls, the signaling data is sent to Call Agent **212** from SS7 network **204** and bearer data is sent to MG **213** from DMS MSC/G-MSC **203**. The MG **213** of this gateway converts media (voice etc.) appropriately. These media packets are sent to SGSN of GPRS-136 network **206** via **Gs'ip** interface. Within the GPRS-136 network **206**, packets are passed to GGSN, and then the packets are passed to PDN/IP network **214** and terminating network **215**, as it has been done for data packets in conventional systems.

For incoming calls, all packets are received by the GGSN from the PDN/IP network **214**, and then are passed to SGSN via GTP. Until this point, the processing of the packets is as done in a conventional GPRS system as in **Figure 1**. In the preferred embodiment, however, instead of just passing this information to BSS, **SGSN** will distribute packets received and forward non-data related packets to the PSTN gateway **213** via **Gs'ip** interface. The MG **213** converts these packets and sends information over T1 links to BSS. Similarly, signaling packets from **SGSN** are received over **Gs'ip** interface and get converted at Call Agent **212** and sent over the **'A'** interface. It should be noted that the conversion of data between the different type of subnetworks may be done by any current method, and is well within the ability of one of ordinary skill in the art.

Note that in both these cases, the vocoder is bypassed. Also, the Terminating Network **215** shown in **Figure 2** can be a Wireless Network, PSTN, or other compatible system.

In these figures, as in **Figure 1**, above, where Terminal Specific Signaling is indicated, the following designations apply:

H.323	=>	H.225 and Q.931
SIP	=>	SAP, SIP or RTSP
BSSx	=>	Supports Voice and/or Circuit-Switched Data
BSSy	=>	Supports Packet Data

MSx => A Mobile Station which Supports Voice and/or Circuit-Switched Data

MSy => A Mobile Station which Supports Packet-Switched Data

Further, solid lines are used to indicate a bearer traffic interface, dashed lines are used to indicate a signaling interface, and a dot/dash line is used to indicate a new bearer traffic and signaling interface according to the preferred embodiment.

Figures 3-5 are exemplary illustrations of different transactions made over a system as shown in the preferred embodiment of **Figure 2**. **Figure 3** shows a diagram of the delivery of a telephone call or circuit-switched data transaction originating in an ANSI-136-A voice or circuit-switched data mobile station to an IP network or vice versa. Here,the call is routed as described above with relation to **Figure 2**, where the IP network **314**, instead of passing data to a terminating network (as **214** in **Figure 2**), simply routes the data via IP protocol to the remote IP end system **316** and/or to an H.323 terminal **317**.

Figure 4 shows a diagram of the delivery of a telephone call or circuit-switched data transaction originating in an ANSI-136-A voice or circuit-switched data mobile station to another ANSI-136/ANSI-41 network (or vice versa) via an IP network. Here, the call is routed as described above with relation to **Figure 2**, where the terminating network is an ANSI-136/ANSI-41 network. After the call is routed to PSTN Gateway **423** from the GGSN of GPRS-136 network **406**, it is passed over an SS7 network **418**/PSTN **419** to the ANSI-136 mobile switching center **420**. From here, it is passed over the **A** interface and T1 to the BSSx **421**, and over the air to the ANSI -136 mobile station MSx **422**.

Figure 5 shows a diagram of the delivery of a telephone call or circuit-switched data transaction originating in an ANSI-136-A voice or circuit-switched data mobile station to a Circuit-Switched Network (SCN) such as PSTN, ISDN via an IP network. Here, the call is routed as described above with relation to **Figure 2**, where the

terminating network is a PSTN. After the call is routed to PSTN Gateway **525** from the GGSN of the GPRS-136 network **506**, it is passed to the PSTN **519**, then to a standard POTS switch **523** and telephone **524**.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

Claims

1. A communications network, comprising:

a circuit-switched communications subnetwork;

a packet-switched subnetwork,

a Internet Protocol-based communications subnetwork, connected to send and receive data between the circuit-switched subnetwork and the packet-switched subnetwork; and

wherein the Internet Protocol-based subnetwork communicates both signal and bearer traffic for voice and data communications.

2. The network of claim 1, wherein the circuit-switched subnetwork includes an SS7 network.

3. The network of claim 1, wherein the packet-switched subnetwork includes a GPRS-136 network.

4. The network of claim 1, wherein the packet-switched subnetwork includes a GPRS-136HS network.

5. The network of claim 1, wherein the packet-switched subnetwork includes a EGPRS network.

6. The network of claim 1, further comprising a second Internet Protocol-based communications subnetwork connected to send and receive data from the packet-switched subnetwork.

7. The network of claim 1, further comprising a second circuit-switched subnetwork connected to send and receive data from the Internet Protocol-based subnetwork.

8. The network of claim 1, further comprising a public service telephone network connected to send and receive data from the packet-switched subnetwork.

9. The network of claim 1, wherein the circuit-switched subnetwork is configured to send and receive data from a wireless station.

10. The network of claim 1, wherein the circuit-switched subnetwork is configured to send and receive voice communications from a wireless station.

11. A method for communicating between electronic devices, comprising:

receiving a first data, from a mobile station, in a circuit-switched network;

converting the first data in to a second data, said second data being comprised of multiple data packets;

sending the second data over an Internet Protocol-based network;

receiving the second data in a packet-switched network; and

sending the second data to a terminating network.

12. The method of claim 11, wherein the circuit-switched subnetwork includes an SS7 network.

13. The method of claim 11, wherein the packet-switched subnetwork includes a GPRS-136 network.

14. The method of claim 11, wherein the packet-switched subnetwork includes a GPRS-136HS network.

15. The method of claim 11, wherein the packet-switched subnetwork includes a EGPRS network.

16. The method of claim 11, wherein the terminating network includes a second Internet Protocol-based communications subnetwork.

17. The method of claim 11, wherein the terminating network includes a second circuit-switched subnetwork.

18. The method of claim 11, wherein the terminating network includes a public service telephone network.

19. The method of claim 11, wherein the circuit-switched subnetwork communicates with the mobile station by wireless communications.

20. The method of claim 11, wherein the circuit-switched subnetwork is configured to send and receive voice communications from the mobile station.


110
109
Terminal Equipment
PDN
105
Terminating Network
106
GGSN
[GTP]
SGSN
GPRS-136 Network
ISUP
IMT
103
104
SS7 Network
STP
DMS-MSC/G-MSC
Vocoder
Gs'
Gb'
102
A
T1
BSSx
108
BSSy
air
air
101
MSx
107
MSy

Fig. 1


Terminating Network
215
Packets
PDN/IP Network
214
Packets
PSTN Gateway
212
Device Control Protocol
213
211
Call Agent
Media Gateway
IP Network
206
GGSN
[GTP]
SGSN
GPRS-136 Network
[RTP]
Gs'IP
ISUP
IMT
203
204
SS7 Network
STP
DMS-MSC/G-MSC
Gs'
Gb'
202
A
T1
BSSx
208
BSSy
Vocoder
air
air
201
MSx
207
MSy

Fig. 2


Remote IP End System
316
H.323 Terminal
317
IP Network
314
Packets
Packets
PSTN Gateway
312
Device Control Protocol
311
313
Call Agent
Media Gateway
IP Network
306
GGSN
[GTP]
GPRS-136 Network
[RTP]
Gs'IP
SGSN
ISUP
IMT
303
304
SS7 Network
STP
DMS-MSC/G-MSC
Gs'
Gb'
302
A
T1
BSSx
308
BSSy
Vocoder
air
air
301
MSx
307
MSy

Fig. 3


SS7 Network
404
STP
DMS-MSC/G-MSC
Vocoder
IMT
403
ISUP
411
Device Control Protocol
PSTN Gateway
412
413
Call Agent
Media Gateway
IP Network
[RTP]
Gs'IP
406
GGSN
[GTP]
SGSN
GPRS-136 Network
Packets
414
IP Network
Call Agent
Media Gateway
Device Control Protocol
PSTN Gateway
423
SS7 Network
ISUP
PSTN
419
STP
DMS-MSC/G-MSC
420
A
T1
421
BSSx
422
MSx
air
A
T1
402
BSSx
401
MSx
air
Gs'
Gb'
408
BSSy
407
MSy
air

Fig. 4


SS7 Network
ISUP
STP
DMS-MSC/G-MSC
IMT
503
Vocoder
T1
A
BSSx
502
air
MSx
501
Gs'
BSSy
508
air
MSy
507
Gb'
Gs'IP
[RTP]
SGSN
[GTP]
GGSN
506
GPRS-136 Network
Packets
IP Network
514
Device Control Protocol
PSTN Gateway
525
Call Agent
Media Gateway
Device Control Protocol
513
PSTN Gateway
512
Call Agent
Media Gateway
IP Network
511
519
PSTN
523
Telephone Switch
524
Phone

Fig. 5

INTERNATIONAL SEARCH REPORT

Int nal Application No
PCT/US 99/27400

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04L12/56 H04L12/28 H04M7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04L H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 742 905 A (BROCKMAN JAMES JOSEPH ET AL) 21 April 1998 (1998-04-21) column 1, line 11 - line 43; figure 3 column 5, line 28 -column 6, line 10 column 24, line 31 -column 25, line 30	1-20
X	WO 97 16007 A (SAKSANEN PAULI ;FINLAND TELECOM OY (FI); KARHAPAEAE TUOMO (FI)) 1 May 1997 (1997-05-01) page 3, line 21 -page 4, line 23 page 5, line 22 -page 6, line 9 page 10, line 31 -page 12, line 32	1-20
A	WO 98 19438 A (ERICSSON TELEFON AB L M) 7 May 1998 (1998-05-07) page 8, line 3 -page 9, line 28; figure 1	3-5, 13-15

-/--

[X] Further documents are listed in the continuation of box C.

[X] Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
2 May 2000	15/05/2000

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Brichau, G

3

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

In nal Application No
PCT/US 99/27400

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 44701 A (ERICSSON TELEFON AB L M) 8 October 1998 (1998-10-08) page 6, line 20 -page 7, line 10; figure 1 page 8, line 17 -page 9, line 24	1,11

3

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

Ir ɔnal Application No
PCT/US 99/27400

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5742905 A	21-04-1998	CA 2199802 A	28-03-1996
		EP 0782805 A	09-07-1997
		JP 9511884 T	25-11-1997
		WO 9609714 A	28-03-1996
		US 5742668 A	21-04-1998
WO 9716007 A	01-05-1997	AU 7302596 A	15-05-1997
		FI 955810 A	26-04-1997
WO 9819438 A	07-05-1998	SE 510664 C	14-06-1999
		AU 4888897 A	22-05-1998
		BR 9712387 A	31-08-1999
		CN 1235727 A	17-11-1999
		EP 0928535 A	14-07-1999
		SE 9603948 A	30-04-1998
WO 9844701 A	08-10-1998	AU 6934798 A	22-10-1998
		EP 0972393 A	19-01-2000
		NO 994222 A	30-11-1999